

# Technical data sheet

## Solid Wood Flooring

	LaStrada	Solido-Click	Trendtime 1	Trendtime 2
<b>Product quality</b>				
Formats / mm	as stated in price list	as stated in price list	as stated in price list	as stated in price list
Pieces / m <sup>2</sup> per pack	as stated in price list	as stated in price list	as stated in price list	as stated in price list
Packs / m <sup>2</sup> per pallet	as stated in price list	as stated in price list	as stated in price list	as stated in price list
Weight per pack / pallet in kg	as stated in price list	as stated in price list	as stated in price list	as stated in price list

### Functional / Surface quality (Test standard)

		"Lacquer-finish"	"Oil-impregnation"
Geometric qualities (EN 13 990)	Coniferous wood	fulfilled	fulfilled
Geometric qualities (EN 13 226)	Hardwood	fulfilled	fulfilled
Chemical resistance (EN 13 442)		char. value 5	char. value 5
Scraping with furniture feet (EN 424)		no visible changes	no visible changes
Resistance to roller castors on chairs (EN 425)	Coniferous wood	chairmat	chairmat
Resistance to roller castors on chairs (EN 425)	Hardwood	fulfilled * <sup>1</sup>	fulfilled * <sup>1</sup>
Sliding friction (EN 13893)		$\mu \geq 0.35$	$\mu \geq 0.35$
Slip resistance, inclined plane (DIN 51130)		R 9	R 9

### Environment

Biological durability (DIN EN 460)	durable for indoor use
Room climate	Natural humidity balancing capacities of wood are beneficial to room climate (50 - 65% rel. at approx. 20° C)
Disposal:	material and reusable energy source
AltholzV, KrW-/AbfG, Test conditions for secondary fuels	

### Physical quality

Heat penetration rate	Temperature balancing on skin contact/ feels warm on feet
Flammability EN 13501-1	<a href="http://www.parador.de">www.parador.de</a>

### Certificates / Test reports

LGA "Quality certificate"	No. 1092	No. 1092	No. 1092	No. 1092
LGA Test report on the quality certificate	IWQ MBL 734 1812	IWQ MBL 734 1812	IWQ MBL 734 1812	IWQ MBL 734 1812

\*<sup>1</sup> We recommend the use of a conventional chairmat.